



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/768,851	01/23/2001	Kenichi Sanpei	450100-02949	3091

20999 7590 10/16/2007  
FROMMER LAWRENCE & HAUG  
745 FIFTH AVENUE- 10TH FL.  
NEW YORK, NY 10151

EXAMINER
----------

MISLEH, JUSTIN P

ART UNIT	PAPER NUMBER
----------	--------------

2622

MAIL DATE	DELIVERY MODE
-----------	---------------

10/16/2007

PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

<b>Office Action Summary</b>	<b>Application No.</b> 09/768,851	<b>Applicant(s)</b> SANPEI, KENICHI	
	<b>Examiner</b> Justin P. Misleh	<b>Art Unit</b> 2622	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 31 July 2007.
- 2a) ☒ This action is **FINAL**.                      2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1 - 20 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1 - 20 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All    b) ☐ Some \*    c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- \* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- |  |   |
|--|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892)   | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)                       | 5) <input type="checkbox"/> Notice of Informal Patent Application                       |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)<br>Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____  |

## DETAILED ACTION

### *Response to Arguments*

1. Applicant's arguments filed July 31, 2007 have been fully considered but they are not persuasive.
2. Applicant argues, "Applicant submits that there is no teaching or suggestion an image photographing apparatus comprising a pulse counter circuit for receiving instructions from said control means indicating a quantity of rows that are not to be read out and are read using a high speed clock and setting a value in response to the quantity of rows that are not to be read out, wherein when the quantity of rows that are not to be read out equals a predetermined value of counted rows, output signals are generated to control a switching unit which switches from the high speed clock to a normal vertical clock, wherein the normal vertical clock corresponds to a read out period where horizontal lines corresponding to the detection area are read out, as recited in claim 1."
3. The Examiner respectfully disagrees with Applicant's position. Figures 5 and 8A and column 10 (lines 1 – 22), of Nishizawa et al., clearly disclose, a lower invalid region, a central valid region, and an upper invalid region and a counter (CT) for counting the number of input clock signals to be applied to the vertical scanning registers and stores what vertical scanning line is being scanned. Thus, contrary to Applicant's assertion, Nishizawa et al. indeed teach, "an image photographing apparatus comprising a pulse counter circuit for receiving instructions from said control means indicating a quantity of rows that are not to be read out and are read using a high speed clock and setting a value in response to the quantity of rows that are not to be read

Art Unit: 2622

out, wherein when the quantity of rows that are not to be read out equals a predetermined value of counted rows, output signals are generated to control a switching unit which switches from the high speed clock to a normal vertical clock, wherein the normal vertical clock corresponds to a read out period where horizontal lines corresponding to the detection area are read out.”

### *Claim Objections*

4. **Claim 7** is objected to because of the following informalities: lack of clarity and precision.

The claim recites, therein, “a control means also controls the imaging device when the still image is being photographed.” (emphasis added by Examiner).

Reciting “also” implies a previously recited “control means” for controlling some other component; however, Parent Claim 6 and dependent Claim 7 do not previously require a control means for controlling anything.

Therefore, the language recited above presents a lack of clarity and precision. The Examiner recommends changing the recited language to “a control means for controlling the imaging device when the still image is being photographed.”

For examination purposes, the language will be interpreted according to the recommendation. **Appropriate correction is required.**

### *Claim Rejections - 35 USC § 103*

5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

Art Unit: 2622

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

6. **Claims 1 – 20** are rejected under 35 U.S.C. 103(a) as being unpatentable over Parulski et al. (US 5,668,597) in view of Nishizawa et al. (US 4,841,369).

**NOTE:** The Examiner notes that Claims 1 and 6 appear to be corresponding apparatus and method claims, respectively; the Examiner further notes that Claims 11 and 16 also appear to be corresponding apparatus and method claims, respectively. Accordingly, Claims 1 and 6 will be rejected together and Claims 11 and 16 will be rejected together.

Moreover, Claims 2, 7, 12, and 17 are substantially and substantively the same; accordingly, they will be rejected together. Further, Claims 3, 8, 13, and 18 are substantially and substantively the same; accordingly, they will be rejected together. Further, Claims 4, 9, 14, and 19 are substantially and substantively the same; accordingly, they will be rejected together. Further, Claims 5, 10, 15, and 20 are substantially and substantively the same; accordingly, they will be rejected together.

7. For **Claims 1 and 6**, Parulski et al. disclose, as shown in figures 1, 4, 5, 8, and 9 and as stated in columns 4 (lines 49 – 59), 5 (lines 54 – 67), 6 (lines 1 – 14, 19 – 22, and 26 – 33), 8 (lines 6 – 67), and 9 (lines 1 – 8), an image photographing apparatus and method of operating thereof for photographing a still image, comprising:

a scanning imaging device (sensor 20; see figures 1 and 4) for generating image signals;  
and  
a control means (processor section 35 and timing control section 27; see figure 1) for using the image signals generated by said imaging device (sensor 20) to adjust the still image .

Art Unit: 2622

during at least one control period before photographing (As shown in figure 9, the claimed “photographing” is in the step “Integrate Final Image”; the claimed “adjust the still image” corresponds to all the steps prior to the “Integrate Final Image Step”; one iteration of the “Focus Acceptable” loop corresponds to the claimed “at least one control period”)., said control means (processor and timing sections 35 and 27) defining a single detection area (central focusing area 66) which is both vertically and horizontally limited within said imaging device (The total image detection area 66 and 68 of image sensor 20 is limited by the left/right and top/bottom edges of the sensor; As shown in figure 1, the central focusing area 66 is within those bounds.) and reading only the image signals within the single detection area out (66) of said imaging device (During a focusing operation, Parulski et al. only reads out signal charges within the central focusing area 66 and dumps the rest of the charges using the “fast flush”; see figure 9), the read image signals being used to adjust the still image before photographing (“Integrate Final Image” step”) and a control period (“non-used lines are quickly flushed”) of said control means being set in correspondence within a read-out period (“fast flush”) associated with said single detection area (see column 5, lines 54 – 66; and also see explanation below).

As shown in figure 4, “only a small number lines in- the central focusing area 66 of the image are used to provide the focus determination input data.” As shown in figure 5, “the average contrast could be computed for a center region 80, a left central region 82, and the right central region 84.” In figure 4, the detection area is vertically limited to a small number of lines and horizontally limited by the pixel plane (as in Applicant’s figure 4) and further, in figure 5, the detection area is vertically limited to a small number of lines and horizontally limited to central regions.

On column 8 (line 39) – column 9 (line 9), Parulski et al. indicates that the AF mode lasts for an indefinite period of time and after that indefinite period of time a final image is then integrated. More specifically, Parulski et al. states, “the process of integrating and reading out the focus image is then repeated – numerous times as the lens focus is adjusted until it provides the maximum average contrast – the focus is acceptable.” Therefore, the control means cannot integrate the final image until the focus is acceptable – i.e. the control means control period switchover (from AF period to still image capture period) is determined by the read-out period of the detection area.

Finally, Parulski et al. indicate that the central focusing area (66) is read-out according to the line-skipping patterns of figures 10 and 11. Parulski et al. further indicate that to read-out in such a pattern, the sensor timing circuit (28) operates according the timing diagram shown in figure 12. Parulski et al., also state in column 8 (lines 1 – 5), “the advantage ... [is] to reduce the amount of data that must be handled from the central focusing area 66”. Parulski et al. additionally indicate (see column 5, lines 54 – 66) that, “non-used lines are quickly flushed”.

While Parulski et al. disclose a timing control section (27); the particulars of the sensor timing circuit (28) or the control interface (52) are not disclosed. Accordingly, Parulski et al. do not teach a pulse counter circuit for receiving instructions from said control means indicating a quantity of rows that are read using a high speed clock and setting a value in response to the quantity of rows, wherein when the quantity of rows equals a predetermined value of counted rows, output signals are generated to control a switching unit which switches from the high speed clock to a normal vertical clock.

On the other hand, Nishizawa et al. also disclose an image photographing apparatus and method of operating thereof for reading out a single detection area within the image sensor.

Nishizawa et al. specifically show, in figures 5 and 8A, an image sensor (CHI) and a control means (collectively clock pulse generator CPG and registers reg2 and reg1) for reading out the single detection area (“valid” region). Nishizawa et al. further teach, as stated in column 10 (lines 1 – 63), a pulse counter circuit (collectively pulse counter CT and comparators cmp2 and cmp1) receiving instructions (“REG1 stores a constant vi ... a comparator CMP1 compares and stores the relation between the levels ... of REG1 and the counter CT; see column 10, lines 20 – 32) from said control means (REG1 is part of the control means) indicating a quantity of rows that are not to be read out and are read using a high speed clock (“since the gates ... are open until the value of the counter CT takes 121, the vertical scanning register Vreg is derive at a high speed”; see column 10, lines 33 – 39) and setting a value in response to the quantity of rows that are not to be read out (“the logic [from the comparator CMP1] is inverted to ‘0’”; see column 10, line 34).

Nishizawa et al. further, as also stated in column 10 (lines 20 – 34), teach wherein when the quantity of rows that are not to be read out (“the value of the counter CT ...”) equals a predetermined value of counted rows (“... takes 121”), output signals are generated to control a switching unit which switches from the high speed clock to a normal vertical clock (“the value of the counter CT takes 121, the vertical scanning register Vreg is driven at a high speed by the horizontal scanning clock signals H1 and H2 and after the 122-th vertical scanning by the ordinary vertical scanning clock signals V1 and V2”; also see column 10, lines 56 – 57) and, accordingly, “the normal vertical clock corresponds to a read out period where horizontal lines



corresponding to the detection area are read out.

Therefore, at the time the invention was made, it would have obvious to one with ordinary skill in the art to have included the pulse counter circuit for receiving instructions indicating a quantity of rows that are read using a high speed clock and when the quantity of rows equals a predetermined value of counted rows, output signals are generated to control a switching unit which switches from the high speed clock to a normal vertical clock (as taught by Nishizawa et al.) in the image photographing apparatus and corresponding method of operating thereof for only reading image signals within a single detection area (disclosed by Parulski et al.) for the advantage of providing *a solid state image pickup apparatus for exclusive use (e.g., pattern recognition with a narrow image pickup range) capable of high-speed operation* (see Nishizawa et al.; column 1, lines 26 – 36).

8. For **Claims 11 and 16**, Parulski et al. disclose, as shown in figures 1, 4, 5, 8, and 9 and as stated in columns 4 (lines 49 – 59), 5 (lines 54 – 67), 6 (lines 1 – 14, 19 – 22, and 26 – 33), 8 (lines 6 – 67), and 9 (lines 1 – 8), an image photographing apparatus and method of operating thereof for photographing a still image, comprising:

a scanning imaging device (sensor 20; see figures 1 and 4) for generating image signals;  
and

a control means (processor section 35 and timing control section 27; see figure 1) for using the image signals generated by said imaging device (sensor 20) to adjust the still image during at least one control period before photographing (As shown in figure 9, the claimed “photographing” is in the step “Integrate Final Image”; the claimed “adjust the still image” corresponds to all the steps prior to the “Integrate Final Image Step”; one iteration of the “Focus

Art Unit: 2622

Acceptable” loop corresponds to the claimed “at least one control period”)., said control means (processor and timing sections 35 and 27) defining a single detection area (central focusing area 66) which is both vertically and horizontally limited within said imaging device (The total image detection area 66 and 68 of image sensor 20 is limited by the left/right and top/bottom edges of the sensor; As shown in figure 1, the central focusing area 66 is within those bounds.) and reading only the image signals within the single detection area out (66) of said imaging device (During a focusing operation, Parulski et al. only reads out signal charges within the central focusing area 66 and dumps the rest of the charges using the “fast flush”; see figure 9), the read image signals being used to adjust the still image before photographing (“Integrate Final Image” step”).

As shown in figure 4, “only a small number lines in- the central focusing area 66 of the image are used to provide the focus determination input data.” As shown in figure 5, “the average contrast could be computed for a center region 80, a left central region 82, and the right central region 84.” In figure 4, the detection area is vertically limited to a small number of lines and horizontally limited by the pixel plane (as in Applicant’s figure 4) and further, in figure 5, the detection area is vertically limited to a small number of lines and horizontally limited to central regions.

On column 8 (line 39) – column 9 (line 9), Parulski et al. indicates that the AF mode lasts for an indefinite period of time and after that indefinite period of time a final image is then integrated. More specifically, Parulski et al. states, “the process of integrating and reading out the focus image is then repeated – numerous times as the lens focus is adjusted until it provides the maximum average contrast – the focus is acceptable.” Therefore, the control means cannot

Art Unit: 2622

integrate the final image until the focus is acceptable – i.e. the control means control period switchover (from AF period to still image capture period) is determined by the read-out period of the detection area.

Finally, Parulski et al. indicate that the central focusing area (66) is read-out according to the line-skipping patterns of figures 10 and 11. Parulski et al. further indicate that to read-out in such a pattern, the sensor timing circuit (28) operates according the timing diagram shown in figure 12. Parulski et al., also state in column 8 (lines 1 – 5), “the advantage ... [is] to reduce the amount of data that must be handled from the central focusing area 66”. Parulski et al. additionally indicate (see column 5, lines 54 – 66) that, “non-used lines are quickly flushed”.

While Parulski et al. disclose a timing control section (27); the particulars of the sensor timing circuit (28) or the control interface (52) are not disclosed. Accordingly, Parulski et al. do not teach wherein the control means controls at least two scan speeds with a first scan speed being used outside the single detection area and a second scan speed being used within the single detection area, the first scan speed being greater than the second scan speed; and a pulse counter circuit for receiving instructions from said control means indicating a quantity of rows that are read using a high speed clock and setting a value in response to the quantity of rows, wherein when the quantity of rows equals a predetermined value of counted rows, output signals are generated to control a switching unit which switches from the high speed clock to a normal vertical clock.

On the other hand, Nishizawa et al. also disclose an image photographing apparatus and method of operating thereof for reading out a single detection area within the image sensor. Nishizawa et al. specifically show, in figures 5 and 8A, an image sensor (CHI) and a control

Art Unit: 2622

means (collectively clock pulse generator CPG and registers reg2 and reg1) for reading out the single detection area (“valid” region). Nishizawa et al. further teach, as stated in column 10 (lines 1 – 63), a pulse counter circuit (collectively pulse counter CT and comparators cmp2 and cmp1) receiving instructions (“REG1 stores a constant vi ... a comparator CMP1 compares and stores the relation between the levels ... of REG1 and the counter CT; see column 10, lines 20 – 32) from said control means (REG1 is part of the control means) indicating a quantity of rows that are not to be read out and are read using a high speed clock (“since the gates ... are open until the value of the counter CT takes 121, the vertical scanning register Vreg is derive at a high speed”; see column 10, lines 33 – 39) and setting a value in response to the quantity of rows that are not to be read out (“the logic [from the comparator CMP1] is inverted to ‘0’”; see column 10, line 34).

Nishizawa et al. further, as also stated in column 10 (lines 20 – 34), teach wherein when the quantity of rows (“the value of the counter CT ...”) equals a predetermined value of counted rows that are not to be read out (“... takes 121”), output signals are generated to control a switching unit which switches from the high speed clock to a normal vertical clock (“the value of the counter CT takes 121, the vertical scanning register Vreg is driven at a high speed by the horizontal scanning clock signals H1 and H2 and after the 122-th vertical scanning by the ordinary vertical scanning clock signals V1 and V2”; also see column 10, lines 56 – 57).

Therefore, Nishizawa et al. wherein the control means (CPG; REG1 and REG2) controls at least two scan speeds with a first scan speed (“high speed”) being used outside the single detection area (up to count value 121) and a second scan speed (“ordinary vertical clock scanning signals”) being used within the single detection area, the first scan speed being greater

Art Unit: 2622

than the second scan speed and, accordingly, “the normal vertical clock corresponds to a read out period where horizontal lines corresponding to the detection area are read out.

Therefore, at the time the invention was made, it would have obvious to one with ordinary skill in the art to have included the pulse counter circuit for receiving instructions indicating a quantity of rows that are read using a high speed clock and when the quantity of rows equals a predetermined value of counted rows, output signals are generated to control a switching unit which switches from the high speed clock to a normal vertical clock (as taught by Nishizawa et al.) in the image photographing apparatus and corresponding method of operating thereof for only reading image signals within a single detection area (disclosed by Parulski et al.) for the advantage of providing *a solid state image pickup apparatus for exclusive use (e.g., pattern recognition with a narrow image pickup range) capable of high-speed operation* (see Nishizawa et al.; column 1, lines 26 – 36).

9. As for **Claims 2, 7 (please see claim objection above), 12, and 17**, Parulski et al. disclose wherein said control means (processor section 35 and timing control section 27) also controls said imaging device (sensor 20) when the still image is being photographed.

Parulski et al. states, in column 4 (lines 28 – 39), “The output of the image sensor 20 is amplified and processed in an analog gain and sampling (correlated double sampling (CDS)) circuit 32, and converted to digital form in A/D converter 34. The A/D output signal is provided to a processor section 35, which includes a digital processor 36 which temporarily stores the still images in a DRAM memory 38. The digital processor 36 then perform image processing on the still images, and finally stores the processed images on the removable memory card 26 via a

Art Unit: 2622

memory card interface circuit 40, which may use the PCMCIA 2.0 standard interface. An EPROM memory 42 is used to store the firmware which operates the digital processor 36.”

10. As for **Claims 3, 8, 13, and 18**, Parulski et al. disclose wherein said control means (processor section 35 and timing control section 27) determines a start position of the single detection area (central focus area 66) and the amount of image to be read out within the single detection area, and, accordingly, only the image signals within the single detection area (central focus area 66) are read out of the said imaging device (sensor 20).

Parulski et al. states, in column 4 (lines 22 – 28), “Control of the sensor 20 is provided by a timing and control section 27, which specifically includes a sensor timing circuit 28. The sensor timing circuit 28 provides the signals to enable sensor drivers 30, which provides horizontal clocks (H1, H2) and vertical clocks (V1, V2), as well as a signal FDG for activating a drain structure on the sensor 20.”

Furthermore, Parulski et al. states, in column 6 (lines 26 – 34), “In the autofocus mode, the timing and control section 27 controls the fast dump structure 62 to A) eliminate all lines of image charge in the outer area 68 (FIG. 4) outside the central focusing area 66, and B) eliminate at least one line of image charge from the image sensor 20 for every one or more lines of image charge that are transferred to the horizontal register 60 for readout from the central focusing area 66.”

11. As for **Claims 4, 9, 14, and 19**, as stated above, Nishizawa et al. further, as also stated in column 10 (lines 20 – 34), teach wherein when the quantity of rows (“the value of the counter CT ...”) equals a predetermined value of counted rows (“... takes 121”), output signals are generated to control a switching unit which switches from the high speed clock to a normal

Art Unit: 2622

vertical clock (“the value of the counter CT takes 121, the vertical scanning register Vreg is driven at a high speed by the horizontal scanning clock signals H1 and H2 and after the 122-th vertical scanning by the ordinary vertical scanning clock signals V1 and V2”; also see column 10, lines 56 – 57). Therefore, Nishizawa et al. wherein the control means (CPG; REG1 and REG2) controls at least two scan speeds with a first scan speed (“high speed”) being used outside the single detection area (up to count value 121) and a second scan speed (“ordinary vertical clock scanning signals”) being used within the single detection area, the first scan speed being greater than the second scan speed.

Therefore, Nishizawa et al. disclose a high-speed scan in a region before the start position of the single detection area, allows a predetermined-speed scan in the single detection area, and allows only the determined amount of image signals to be read out.

12. As for **Claims 5, 10, 15, and 20**, Parulski et al. disclose wherein, based on the read image signals, at least one of automatic focus control, automatic photographic sensitivity control, and automatic white balance control is performed.

Parulski et al. performs automatic focus control on the read image signals (see figure 9).

### ***Conclusion***

13. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR.1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after

Art Unit: 2622


the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

14. Any inquiry concerning this communication or earlier communications from the Examiner should be directed to Justin P Misleh whose telephone number is 571.272.7313. The Examiner can normally be reached on Monday through Friday from 8:00 AM to 5:00 PM.

If attempts to reach the Examiner by telephone are unsuccessful, the Examiner's supervisor, Lin Ye can be reached on 571.272.7372. The fax phone number for the organization where this application or proceeding is assigned is 571.273.8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

JPM  
October 10, 2007

  
LIN YE  
SUPERVISORY PATENT EXAMINER